

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
24 February 2005 (24.02.2005)


PCT

(10) International Publication Number  
**WO 2005/016611 A3**

- (51) International Patent Classification<sup>7</sup>: **B65G 17/06** (72) Inventors; and  
(75) Inventors/Applicants (for US only): **GULDENFELS, Dieter** [CH/CH]; Im Steinler 18, CH-4148 Pfeffingen (CH). **HIRSCHMANN, Paul, E.** [US/US]; 475 Big Bend Trail, Sugar Hill, GA 30518 (US). **PEACH, Michael, Anthony** [GB/US]; 395 Laura Drive North, Lakewood Heights, Mandeville, LA 70448 (US).
- (21) International Application Number: PCT/US2004/026468
- (22) International Filing Date: 12 August 2004 (12.08.2004)
- (25) Filing Language: English (74) Agents: **PRINCIPE, David, L.** et al.; Hodgson Russ LLP, One M & T Plaza, Suite 2000, Buffalo, NY 14203-2391 (US).
- (26) Publication Language: English
- (30) Priority Data: 60/494,378 12 August 2003 (12.08.2003) US (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
- (71) Applicant (for all designated States except US): **HAB-ASIT AG** [CH/CH]; Römerstrasse 1, CH-4153 Reinach-Basel (CH).

[Continued on next page]

(54) Title: DEVICE FOR RETAINING A HEADED PIVOT ROD



(57) Abstract: A belt module (10), modular belt assembly and method of configuring a modular belt to provide an edge portion for retaining a headed pivot rod (103). The edge portion has a blocking member (70) disposed in a slot (73) and movable between a first open position and a second closed position. In the closed position, the blocking member extends into an edge portion pivot rod opening (51) to prevent the headed pivot rod from exiting the edge portion pivot rod opening. The edge portion pivot rod opening is larger than the first and second pivot rod openings in the first and second link ends of the belt module such that the pivot rod can only be removed in one direction.



PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

- (84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

- (88) **Date of publication of the international search report:**  
18 August 2005

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*